



# TOMRA 3A

## OPTICAL SORTER

**Interested in a free demonstration  
with your own product or require  
more information?**

**Please contact us directly.**

**TOMRA Food EMEA**

Research Park Haasrode 1622  
Romeinse straat, 20  
3001 Leuven  
BELGIUM

Tel: +32 16 396 396  
Fax: +32 16 396 390  
food@tomra.com  
www.tomra.com/food

**TOMRA Food AMERICAS**

875 Embarcadero Drive  
West Sacramento  
California 95605  
U.S.A.

Tel: +1 916 388 3900  
Fax: +1 916 388 3901  
food.us@tomra.com  
www.tomra.com/food

**TOMRA Food APAC**

Unit 1, 20 Anella Ave,  
Castle Hill, 2154  
NSW  
AUSTRALIA

Tel: +61 2 8624 0100  
Fax: +61 2 8624 0101  
food.asia@tomra.com  
www.tomra.com/food

**TOMRA Food CHINA**

1A/E, Rihua Building, No.8,  
Xinfeng 2nd Road, Huli District,  
Xiamen, Fujian, 361006  
P.R.CHINA

Tel: +86 592 572 0780  
Fax: +86 592 572 0779  
food.china@tomra.com  
www.tomra.com/food

Boasting the highest capacity on the market, the TOMRA 3A is the most robust, reliable and cost-effective optical sorter available for growers. Built to last, it is a highly efficient, durable and powerful labor-saving solution specifically developed to provide unrivalled foreign material removal and meet harvest demands. Simple to install, use and maintain, it is an easy fit into the harvest cleaning and grading line and can also be used for out-of-storage sorting.

## SOPHISTICATED TECHNOLOGY. HIGH PERFORMANCE.

The TOMRA 3A employs NIR (Near Infra-Red) multi-spectral sensors for an unobstructed assessment of every object 'in flight', seamlessly identifying between potatoes and foreign material. Color sensors now also enable the detection of unwanted green potatoes. Positioned at the end of the conveyor belt, intelligent finger ejectors achieve superior foreign material and green potato removal with minimum loss of good product.

The strategic combination of multi-spectral pulsed LED illumination technology, high-resolution cameras and TOMRA analysis software ensures the accurate and consistent removal of stones, soil clods, rocks, wood, bone, plastic, glass, metal and rubber.

Enclosed in a fully sealed box, the camera is tolerant of most environmental conditions such as rain, wind, dust and heat while the optical system has no moving parts, making the TOMRA 3A the most mobile, robust and stable sorter available.

Ideal for use with variable incoming crop during harvest, the TOMRA 3A delivers an exceptionally reliable performance allowing harvest to continue even in the most challenging conditions. The TOMRA 3A delivers superior quality by removing foreign material not removed by traditional soil cleaners and trash eliminators further up the line.

## BENEFITS

- **Significant labor reduction**
- **Higher yields and enhanced product quality**
- **Superior foreign material removal and reduced risk of deductions**
- **Unwanted green potato removal**
- **High capacity for quicker harvest (up to 100TPH possible)**
- **Accommodates various soil types and coverages**
- **Optimized design for gentle handling even during fast, high capacity sorts**
- **Reduced storage costs**
- **Consistent long-life accuracy**
- **Quick and easy installation**
- **User-friendly, simple to use and maintain**



## DURABLE. RELIABLE. EASY TO OPERATE.

When it comes to boosting productivity, optimizing efficiency and maximizing value, information is key. Installed with a highly intuitive user touchscreen, the TOMRA 3A ensures monitoring of the sort at a glance. Adjustments, if needed, are quick and simple. The bright, information-rich display also provides a clear, on-screen display of data, empowering the grower with total control over the quality of the sort.

### DIMENSIONS AND SPECIFICATIONS\*

Model	Dimensions				Utilities	
	Width	Length	Height	Infeed Elevation	Power	Air
<b>TOMRA 3A 1200</b>	2 110 mm (83.125")	3 520 mm (138.5")	1 980 mm (78")	1 255 mm (49.5")	3ph+N 4kVA	7 bar
<b>TOMRA 3A 1600</b>	2 510 mm (98.875")	3 520 mm (138.5")	1 980 mm (78")	1 255 mm (49.5")	3ph+N 5kVA	7 bar
<b>TOMRA 3A 2400</b>	3 310 mm (130.5")	3 520 mm (138.5")	1 980 mm (78")	1 255 mm (49.5")	3ph+N 6kVA	7 bar

\*Information shown for reference and may change depending on the actual application.